



- NOTES:
- 1: GEL COAT THICKNESS .020" ±.005.
 - 2: 1ST LAMINATE .125" NOMINAL THICKNESS.
 - 3: BACK & SIDE WALLS REINFORCED WITH WOOD & SINGLE FACED CORRUGATE.
 - 4: BOTTOM REINFORCED WITH WOOD TO MEET 300# LOAD TEST.
 - 5: 2ND LAMINATE COMPLETELY COVERS ALL REINFORCEMENTS PLUS .100" ADDED TO UNREINFORCED AREAS.
 - 6: COMPOSITE CONSISTS OF: A) GELCOAT, B) RESIN, C) GLASS, D) FILLER
 - 7: GRAB BARS & SEATS ARE OPTIONAL.
 - 8: CURTAIN ROD OPTIONAL.
 - 9: ADJUSTING SHOWER HEAD & PRESSURE BALANCING MIXING VALVE - OPTIONAL. SYMMONS 98-1-131-XLB.

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE AS FOLLOWS	
DECIMAL: .XX = ±.010 .XXX = ±.005	FRACTIONAL: ±1/8" ANGULAR: ±1/2°
CAPACITY/ OPERATING LEVEL:	GAL
CAPACITY/ OVERFLOW LEVEL:	GAL
APPROX. UNIT WEIGHT:	LBS
APPROX. SHIPPING WEIGHT:	LBS

<h1>Fiber Care Baths, Inc.</h1> <p>9832 Yucca Rd. Adelanto, CA 92301 Phone: 760-246-0019 Fax: 760-246-5189</p>			TITLE	
			<h2>SHOWER STALL, 3 WALL INSTITUTIONAL</h2>	
DWN	SIZE	MODEL #	REV	
KBP	A	HS38-38BF	N/C	
DATE	SCALE	PAGE	1 OF 1	
5/19/03	NTS			

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FIBER CARE BATHS, INC. ANY REPRODUCTION OR UNAUTHORIZED USE IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FIBER CARE BATHS, INC. IS STRICTLY PROHIBITED. PRODUCT CONFIGURATION, DIMENSIONS, STANDARD ACCESSORIES, MATERIALS COMPOSITION AND CONSTRUCTION ARE SUBJECT TO CHANGE WITHOUT NOTICE.